



712A

P-024-118

MORS P#: (if known)

DEADLINE: 2 MAY 08 Fax to: 703-933-9066




PART I At sub	thor Request - The follosequent publication in the M	owing author(s) request aut DRSS Final Report, for inclu	hority to disclose the following pasion on the MORSS CD and/or	presentation at the next MORS Symposium with posting on the MORS web site.		
Jon Peoble James Rodrigue						
	ganization and address:			Phone: (520) 545-7841		
Raytheon Missile Systems PO Box 11337 Tucson, AZ 85734-1337				Fax: (520) 794-8625		
			04/30/08	Email: Jon_E_Peoble@raytheon.com		
Benefits of Steeper Angle of Fall for Precision Projectiles						
This presentation is believed to be: SECRET CONFIDENTIAL UNCLASSIFIED and will be presented in: Special Session Tutorial Demo CG: A-B-C-D-E-F (Circle one) List all WG(s) #: 12						
This work was performed in connection with a government contract. This presentation is based on material developed by the author as part of company-approved research e.g. IR&D. This presentation was NOT done under a government contract, contains no government information, is wy own work and is approved for public release. YES (Complete Parts I, II, & III) YES (Complete Parts I & III) YES (Complete Parts I only)						
				icer concurs in the assigned classification and the Contracting Officer for approval.		
This work was performed	in connection with Contract #:		let by (Activity):	Dated:		
Contractor Security C	Officers Title:		Organization:			
Printed name;			Complete mailing addre	Complete mailing address:		
	Officer's Signature: 4	Date:	Phone:	FAX;		
PART III Releasing Official/GOV'T Contracting Officer OR Study Sponsor and DoD Directive 5230.24 – Required Applicable Distribution Statement						
The Releasing Official/Government Contracting Officer or Study Sponsor, with the understanding that MORS Symposia are supervised by the OCNO N81, that all attendees have current security clearances of at least SECRET and that no foreign nationals will be present confirms that the overall classification of the presentation is:						
SECRET CONFIDENTIAL UNCLASSIFIED OTHER: and authorizes disclosure at the meeting.						
Classified by: Declassified by: Downgrade to: On:						
Distribution statement A: This presentation/paper is unclassified, approved for public release, distribution untimited, and is exempt from U.S. export licensing and other export approvals under the International Traffic in Arms Regulations (22 CFR 120 et seq.)						
Releasing Official/Gov't Contracting Officer or Study Sponsor's:			Organization:			
Title:			Complete mailing address	Complete mailing address:		
Name:						
Signature: X						
Date:	Email:		Phone:	FAX:		

maintaining the data needed, and of including suggestions for reducing	election of information is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar OMB control number.	ion of information. Send comments arters Services, Directorate for Info	regarding this burden estimate rmation Operations and Reports	or any other aspect of the property of the contract of the con	nis collection of information, Highway, Suite 1204, Arlington	
1. REPORT DATE 01 JUN 2008			3. DATES COVERED			
4. TITLE AND SUBTITLE				5a. CONTRACT	NUMBER	
Benefits of Steeper Angle of Fall for Precision Projectiles				5b. GRANT NUMBER		
				5c. PROGRAM E	ELEMENT NUMBER	
6. AUTHOR(S)			5d. PROJECT NUMBER			
			5e. TASK NUMBER			
			5f. WORK UNIT NUMBER			
7. PERFORMING ORGANI Raytheon Compan	ZATION NAME(S) AND AD	DDRESS(ES)		8. PERFORMING REPORT NUMB	G ORGANIZATION ER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/M NUMBER(S)	ONITOR'S REPORT	
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT ic release, distributi	on unlimited				
	OTES 27. Military Operat ne 10-12, 2008, The				New London,	
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON	
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	UU	15	RESTUNSIBLE FERSUN	

Report Documentation Page

Form Approved OMB No. 0704-0188







Background and Study Objective

Background

- Battlefield has changed since initial requirements for precision projectiles were developed:
 - Counterinsurgency vs. Mobile Armored Warfare
 - Combat among the population vs. on unoccupied terrain
 - Collateral Damage relationship to strategic outcome
- FA is again relevant: cannon-delivered precision fires have been achieved, demonstrated in combat, and early expectations surpassed
- -Requirements have not yet reflected technology capability for AOF.

Study Objective

- Quantify benefits of having steeper Angle of Fall (AOF) for precision projectiles within urban terrain
- Measure of Merits include Engageable Area, Lethality, Operational Effectiveness, and Cost




Effects of Angle of Fall on Engageability of Different Urban Terrains

Methodology: Measuring Effects of Angle of Fall





 Build urban terrain based on real-world measurements of street width, building height, and block sizes

Apply Safe Footprints Shadows to urban terrain for two gun-target lines 4. Measure how much of open terrain is still engageable



2. Calculate Safe Footprint shadow created by each building vs AoF







Urban Terrain Types

City Core



- · Block Size: 340 x 430 meters
- # Roads: 2 (vert.) 3 (horiz)
- Avg. Road Size: 18.5 meters
- Avg. Building Size: 20×20 meters
- Avg. Building Height: 12.2 meters
- Height Std Dev: 6.1 meters
- Avg. Distance **Between Buildings** 8 meters

Commercial



- Block Size: 80 x 330 meters
- # Roads: 2 (vert.) 4 (horiz)
- Avg. Road Size: 18.5 meters
- Avg. Building Size: 15 x 15 meters
- Avg. Building Height: 6.1 meters
- Height Std Dev: 3.05 meters
- Avg. Distance **Between Buildings** 7 meters

Core Periphery



- Block Size: 320 x 260 meters
- # Roads: 3 (vert.) 4 (horiz)
- Avg. Road Size: 16 meters
- Avg. Building Size: 18 x 18 meters
- Avg. Building Height: 7.6 meters
- Height Std Dev: 1.525 meters
- Avg. Distance **Between Buildings** 7 meters

Residential



- Block Size: 270 x 330 meters
- # Roads: 3 (vert.) 7 (horiz)
- Avg. Road Size: 10 meters
- Avg. Building Size: 10×10 meters
- Avg. Building Height: 4.5 meters
- Height Std Dev: 1.525 meters
- Avg. Distance **Between Buildings** 5 meters

Industrial





- Block Size: 610 x 610 meters
- # Roads: 3 (vert.) 3 (horiz)
- Avg. Road Size: 18.5 meters
- Avg. Building Size: 25 x 25 meters
- Avg. Building Height: 9.2 meters
- Height Std Dev: 6.1 meters
- Avg. Distance **Between Buildings** 10 meters

^{1.} Building size/height, road size, and distance between buildings from Marine Corps Warfighting Pub (MCWP) 3-35.3 – Military Operations in Urban Terrain

Analysis: Effects of Angle of Fall on Engageability









- MoE: Measure what percentage of the open area is engageable by indirect fire
 - Open Area is any area not occupied by a building
 - Indirect Fire cannot engage open area if round's angle of fall would clip the nearby building

• Results:

- Steeper AoF can <u>engage more open area</u> in all urban terrain types:
- % more open area engageable in worst case vs. 60°


City Core: 75°: +57.5% 90°: +107.3%
Industrial: 75°: +28.5% 90°: +53.2%
Core Periph: 75°: +24.5% 90°: +45.8%
Residential: 75°: +21.9% 90°: +40.9%
Commercial: 75°: +8.8% 90°: +16.3%

Steeper Angle of Fall enables Indirect Fire to engage significantly more Urban Terrain, especially if ideal Gun Placement is not possible

Methodology: Measuring Effects of Angle of Fall in a Real City



Analysis Questions: Does a steeper Angle of Fall (AoF) provide a tactical advantage in an urban area? How much area is "hidden" by buildings, providing safe havens?








- 1. Use a real-life example of terrain with varying urban areas (Al Fallujah):
 - Residential Sprawl


 Many small buildings, close together
 - City Core (downtown)
 Large / tall buildings
 - **Commercial District** *Large buildings / warehouses*

- 2. Convert terrain into a 3d model.
 - Building size based on highresolution satellite images
 - Building height based on shadow analysis of satellite images and from aggregate data collected from various urban areas
- 3. Use sophisticated graphics programs to cast light down on model at desired AoF.
- 4. Measure the amount of area still engageable
 - Non-Engageable "Safe Footprint" Shadows in red
 - Engageable area in green

Analysis: Effects of Angle of Fall on Engageability







- MoE: Measure what percentage of the open area is engageable by indirect fire
 - Open Area is any area not occupied by a building
 - Indirect Fire cannot engage the open area if the round's angle of fall would clip the nearby building
 - Area Composure:

– Residential:	37% Buildings	63% Open
- City Core:	35% Buildings	65% Open
- Commercial:	37% Buildings	63% Open
- Entire City:	31% Buildings	69% Open

• Results:

- Steeper angles of fall can consistently <u>engage more</u> <u>open area</u> in all Al Fallujah terrain types
- % more open area engageable vs. 60°

- Residential:	75°: +15.2%	90°: +38.6%
- City Core:	75°: +10.9%	90°: +25.9%
- Commercial:	75°: +9.4%	90°: +21.3%
Entire City:	75°: +8.4%	90°: +19.7%


In central Al Fallujah, a round with a steep Angle of Fall enables Indirect Fire to engage significantly more of the city's open area



Effects of Angle of Fall on Lethality, Operational Effectiveness, and Cost

Analysis: Effects of Angle of Fall on Lethality





Comparison of Lethality vs. 60° AoF

AoF	75°	90°
Total Area	+61%	+206%
Lethal Area	+62%	+141%
Pk > .8	+120%	+180%
.8 > Pk > .6	+33%	+189%
.6 > Pk > .4	+58%	+67%
.4 > Pk > .2	+39%	+21%
.2 > Pk > .05	+67%	+272%


Total Area = Area affected by munition


Lethal Area = Measure of effectiveness for particular target/weapon pairing. Computed as the sum of (Pk*Area) across all individual cells in the PkMap.

Increased Angle of Fall results in significantly Increased Lethality


Methodology: Measuring effects of AoF on Operational Effectiveness

Analysis Questions: In urban terrain, what Angle of Fall (AoF) is necessary to put effects on target and to minimize structural collateral damage?





- Targets placed in alleys 0.5 –
 1.5m away from building
- Represents truck "parked" next to building and infantry hugging building wall
- Assume reporting TLE is 10m





- 1. Build the 5 urban terrain templates into JCATS:
 - City Core (downtown)
 - Commercial District
 - Core Periphery
 - Residential Area
 - Industrial Area
- Results based on average across all terrains

- 3. Launch rounds at the targets with varying CEP and AoF. Measure rounds to reach 30% EFD and measure collateral damage.
 - Aimpoints offset from target =
 ½ lethal radius (or middle of Alley if lethal radius too large)
 - Lessens chance of impacting nearby buildings
 - Clipping buildings played

Analysis: Effects of Angle of Fall on Operational Effectiveness







• **Building Heights:**

- Average building height comes from the 5 Urban Terrain Templates
- Max building height is average + 3-sigma variance
 - Sigma values provided in the Urban Terrain templates
- Tactical building height is between average and max
 - Threat would realize capability of projectiles to come over buildings
 - Threat would tactically choose a taller than average building to mitigate this advantage
- <u>MoE</u>: Rounds needed to reach EFD of 30%; Collateral Damage produced from rounds impacting on/near buildings
 - Assumes 10m TLE
 - Rounds will clip building if AoF is too shallow

• Results for the Tactical Case:

Comparison to 60° Angle of Fall

- % fewer rounds vs. Truck: **75°:** -36% **90°:** -66%


<u>% fewer rounds vs. Dismnt:</u> **75°:** -35% **90°:** -62%

% Less Structural Damage: 75°: -34% 90°: -66%

Steeper Angle of Fall provides significant Operational benefits against targets in Urban Terrain; Targets are eliminated with fewer rounds and less Structural Damage is created

Analysis: Effects of Angle of Fall on Cost





 Methodology: Apply costs to the number of rounds required to reach EFD computed by JCATS

• Assumptions:

- Tactical building height results used
- 75° round costs 20% more than 60° round
- 90° round costs 40% more than 60° round

• Results:

- Steeper angle of fall results in significantly less cost
 - Steep angle of fall maximizes lethality
 - Steep angle of fall avoids clipping of buildings
- If 10 missions are fired on each target daily:
 - 75° will save \$363.8k per day
 - 90° will save \$812.7k per day
- To be as cost effective as a round with 90°:
 - A round with 60° would need a unit cost 64% less than the 90° round
 - A round with 75° would need a unit cost 45% less than the 90° round

Steeper Angle of Fall achieves effects for less cost; Cost per Kill much more affordable

